

company:

name: function:

address:

postal code / city:

phone fax: email:

Pumping medium

description:

features:

solids contents	<input type="checkbox"/>	yes	<input type="checkbox"/>	no
crystallizing out	<input type="checkbox"/>	yes	<input type="checkbox"/>	no
risk of past up	<input type="checkbox"/>	yes	<input type="checkbox"/>	no
abrasiv behavior	<input type="checkbox"/>	yes	<input type="checkbox"/>	no

concentration: % pH value:

density: kg/m³ viscosity: mPa s

temperature: °C short term: °C

data

flow rate: l/min m³/h kg/h

discharge pressure: bar m

Inlet height: m NPSH available: m

self priming: yes no suction lift: m

suction line: DN: mm height: m lenght: m bow: pce. valves: pce.

Discharge line: DN: mm height: m lenght: m bow: pce. valves: pce.

Pump details

materials : 1.4435 (316L)

shaft sealing: mechanical seal magnetic coupling

connections:

drive

power: kW

rotating speed: 3000 rpm 1500 rpm rpm

voltage: 230 / 400 Volt 400 / 690 Volt Volt

frequency: 50 Hz 60 Hz Hz

PTC sensor: yes no

Ex- protection: EEx e II T3 EEx de IIc T4

remarks

date: signature: